

錚鑫機械工程股份有限公司

公司地址：新竹市中華路四段 500 號 TEL:03-5388015 FAX:03-5302033

SUS 304 ETFE Coating 風管重量表 日期:95\10\16

項次Item	管徑Size mm	厚度(mm) Thickness	直管Duct 1M/Kg	直管Duct 1.2M/Kg	90° 彎頭 1D/Kg	45° 彎頭 1D/Kg	法蘭規格	法蘭/組 1組/Kg
1	φ 100	1	2.70	3.23	0.58	0.42	25*17*3.0	0.60
2	φ 150	1	4.04	4.84	1.25	0.67	25*17*3.0	1.38
3	φ 200	1	5.38	6.44	1.98	1.15	25*17*3.0	1.75
4	φ 250	1	6.72	8.04	2.99	1.69	38*17*3.0	1.90
5	φ 300	1	8.06	9.64	3.89	2.03	38*17*3.0	2.40
6	φ 350	1	9.40	11.24	5.26	2.72	38*17*3.0	3.80
7	φ 400	1	10.74	12.84	6.84	3.53	38*17*3.0	4.60
8	φ 450	1	12.07	14.44	8.62	4.43	38*38*3.0t	5.20
9	φ 500	1	13.41	16.04	10.61	5.44	38*38*3.0t	6.00
10	φ 550	1	14.75	17.64	12.81	6.55	38*38*3.0t	6.60
11	φ 600	1	16.09	19.25	15.21	7.76	38*38*3.0t	7.20
12	φ 650	1	17.43	20.85	17.82	9.08	38*38*3.0t	8.00
13	φ 700	1	18.77	22.45	20.63	10.50	38*38*3.0t	8.40
14	φ 750	1	20.11	24.05	23.65	12.02	38*38*3.0t	9.00
15	φ 800	1	21.45	25.65	26.87	13.65	38*38*3.0t	9.60
16	φ 850	1	22.78	27.25	30.31	15.38	38*38*3.0t	10.40
17	φ 900	1	24.12	28.85	33.94	17.21	38*38*3.0t	11.00
18	φ 950	1.2	30.29	36.23	44.96	22.78	38*38*3.0t	11.60
19	φ 1000	1.2	31.89	38.14	49.78	25.20	38*38*3.0t	15.40
20	φ 1050	1.2	33.48	40.04	54.84	27.75	38*38*3.0t	15.80
21	φ 1100	1.2	35.07	41.95	60.15	30.42	38*38*3.0t	16.80
22	φ 1150	1.2	36.67	43.85	65.71	33.21	38*38*3.0t	17.60
23	φ 1200	1.2	38.26	45.76	71.51	36.13	38*38*3.0t	18.40
24	φ 1250	1.2	39.85	47.66	77.56	39.17	38*38*4.0t	21.20
25	φ 1300	1.5	51.36	61.43	103.91	52.46	38*38*4.0t	20.20
26	φ 1350	1.5	53.34	63.79	112.01	56.53	38*38*4.0t	21.20
27	φ 1400	1.5	55.31	66.15	120.42	60.75	38*38*4.0t	22.00
28	φ 1450	1.5	57.28	68.52	129.13	65.12	38*38*4.0t	22.80
29	φ 1500	1.5	59.26	70.88	138.14	69.65	38*38*4.0t	41.60
30	φ 1600	1.5	63.17	75.55	156.88	79.06	50*50*4.0t	44.20
31	φ 1700	1.5	67.11	80.27	177.02	89.17	50*50*4.0t	47.40
32	φ 1800	1.5	71.06	85.00	198.38	99.88	50*50*4.0t	50.40
33	φ 1900	2	99.15	118.59	292.06	147.00	50*50*4.0t	53.20
34	φ 2000	2	104.37	124.83	323.50	162.77	50*50*4.0t	56.60
35	φ 2100	2	109.59	131.07	356.55	179.35	50*50*5.0t	59.40
36	φ 2200	2	114.81	137.32	391.21	196.73	50*50*5.0t	62.20
37	φ 2300	2	120.02	143.56	427.48	214.92	50*50*5.0t	65.00
38	φ 2400	2	125.24	149.80	465.35	233.90	50*50*5.0t	67.80